

Industrially produced roofing system Kerto-Ripa™ for non-residential buildings

Case: Department store in Raisio, Finland

30 000 m² of commercial space weather-protected in 9 weeks



finnforest

Kerto-Ripa roof element




- Kerto-Ripa roof element is a ready-to-install building component for large roofs.
- Kerto-Ripa roof element is ideal for long spans (12 to 18 meters). The maximum cost-efficiency with ordinary frame solutions is reached, when every second main beam with columns and foundations can be deleted.
- The element is very light in weight. Therefore, heavy concrete beams can easily be replaced with glulam beams (max. length 34 meters).

Kerto-Ripa roof element

- Kerto-Ripa roof element is planned according to the customer's needs. The frame of the element is made of Kerto® LVL. The element is delivered with a bitumen roofing felt or a PVC cover. It is equipped with a thermal insulation most suitable for the project.
- Kerto-Ripa element is produced at the mill, and delivered just in time. On site, the element is fixed into the frame, as well as the joints between the elements.
- Installation is very effective: In one day, we can install up to 1.000m² of ready, water-tight and warm-insulated roof.

Roof ready in one delivery:
Weather-proof roofing – thermal insulation – ceiling
panel on the underside

Kerto-Ripa™ box slab roof element



Structure of Kerto-Ripa™ box slab roof element

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Production of Kerto-Ripa™ element in conditioned mill environment, Oct. to Dec. 2007

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Production of Kerto-Ripa™ element in conditioned mill environment, Oct. to Dec. 2007

◀ Start

Structure ■

Production ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Production of Kerto-Ripa™ element in conditioned mill environment, Oct. to Dec. 2007

◀ Start

Structure ■

Production ■ ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Production of Kerto-Ripa™ element in conditioned mill environment, Oct. to Dec. 2007

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Installation starts on 15th October, 2007

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Installation starts on 15th October, 2007

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



16 m (max. 18 m)

Installation starts on 15th October, 2007

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



The inside work continues immediately

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Construction site remains clean

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



16 000 m² of roof is installed in 9 weeks

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Fixing the element in load-bearing beams

◀◀ Start

Structure

Production ☒ ☐ ☐ ☐


Installation ☐ ☐ ☐ ☐ ☐ ☐ ☒ ☐

Details ■ ■ ■ ■ ■ ■



Summary ■ ■

Contact

finnforest



◀ Start Structure ■ Production ■ ■ ■ ■ Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■ Details ■ ■ ■ ■ ■ ■ ■ ■ Summary ■ ■ Contact ■



Buckling of primary beams is prevented with roof elements

◀ Start

Structure ■

Production ■ ■ ■ ■


Installation ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■ ■

Contact ■

finnforest



Roof saddle connection

◀ Start

Structure ■

Production ■ ■ ■ ■


Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Finishing the joint between two elements

◀ Start

Structure ■

Production ■ ■ ■ ■


Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Finishing the PVC roofing and the structure of the gutter

◀ Start

Structure ■

Production ■ ■ ■ ■


Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest



Connection between roof and end wall

◀ Start

Structure ■

Production ■ ■ ■ ■



Installation ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■ ■ ■ ■ ■

Summary ■ ■


Contact ■

finnforest



Connection between roof and side wall


Carbon footprint, kg CO₂/ m² of roof of alternative materials




Carbon footprint

Comparison in terms of CO₂

The CO₂ emissions of different structure alternatives, compared with emissions of a car (160 g CO₂ / km)



The saved emissions of the 16.000 m² roof equals to
4.500.000 to 6.900.000 kilometres of car-driving



In addition:

Wood acts as a carbon storage,

not included in this analysis!

Why to choose the Kerto-Ripa™ roof element?

1. Cost-efficient

- Kerto-Ripa™ box slab is **five times lighter** in weight than the TT concrete slab with a span of 16 meters
 - Smaller size concrete main beams could be used and less piles were needed for the foundation
 - Long spans: even 18 meters
- Quicker construction: cladding on underside of element, thermal insulations and roof covering are installed already on mill.
 - Short installation time
 - Next phases of construction can continue immediately, in dry conditions
- The total construction time is shorter
=> Saving in time and money

Summary

Why to choose the Kerto-Ripa™ roof element?

2. Environmental friendly

- Carbon footprint ~40 % less than with alternative materials
- Wood acts as a carbon storage and is a completely renewable building material.

=> Saving in CO₂ emissions

- Thermal insulation of the roof can be easily increased with a very moderate cost.

E.g. an increase of 5 cm costs ~2 eur/m². Advantage of 20% better thermal insulation

=> Saving in energy

Why to choose the Kerto-Ripa™ roof element?

3. Fire safe

- Fire resistance R60 minutes and A1-s1,d0 reaction to fire classification

4. Verified building physics

- Thermal and moisture behaviour of the structures were carefully tested by the Technical University of Tampere, Finland (Report 1562/T)

5. Certified

- Kerto-Ripa™ roof element has the European technical approval ETA-07/0029 and CE marking.



For more information, please contact

Jouni Hakkarainen

Finnforest, Building Solutions

Phone +358 50 598 9611

Jouni.hakkarainen@finnforest.com

www.finnforest.com

Contact

◀ Start

Structure ■

Production ■ ■ ■ ■

Installation ■ ■ ■ ■ ■ ■ ■ ■

Details ■ ■ ■ ■ ■ ■

Summary ■ ■

Contact ■

finnforest